



0416

Outokumpu Chrome Oy
95490 Tornio
23
0416-CPR-3591-04

DECLARATION OF PERFORMANCE: OKTO-murske 0-4, 2023

EN 13242:2002+A1:2007

Aggregates for unbound and hydraulically bound materials for use in civil engineering work and road construction

Essential characteristics	Performance
Particle size	0/4 mm
Category	G _F 85, G _T 20
Particle density	3,15 ... 3,62 Mg/m ³
Cleanliness	f ₇
Percentage of crushed and broken surfaces	NPD
Resistance to fragmentation/crushing	NPD
Volume stability	NPD
Water absorption	WA ₂₄ 1
Composition/content	SiO ₂ 30 % Al ₂ O ₃ 26 % MgO 23 % Cr 8 % Fe 4 % CaO 2 %
Total sulfur	S ₁
Resistance to attrition	NPD
Dangerous substances:	NPD
Emission of radioactivity	
Release of heavy metals	
Release of polyaromatic carbons	
Release of other dangerous substances	
Durability against weathering	NPD
Durability against freezing and thawing	NPD

Additional information

Typical grading and tolerances	8 mm	100 %	100 %
	5,6 mm	99 %	98 - 100 %
	4 mm	95 %	90 - 99 %
	2 mm	70 %	50 - 90 %
	1 mm	50 %	30 - 70 %
	0,063 mm	4 %	< 7 %